

EMT

Raintight Steel Compression Couplings

Features:

- The only steel compression fitting, UL Listed Raintight
- Steel locknuts
- Heavy steel walls
- Raintight
- Concrete tight
- Blue nut eases identification
- RoHS compliant
- Suitable for use outdoors

Standard Materials:


- Steel
- Nylon compression ring

Standard Finish:

- Zinc plated

Applicable Third Party

- Standards:**
 UL Standard: 514B
 Fed. Spec. W-F-408E
 NEMA: FB-1



CATALOG NUMBER	TRADE SIZE	KO SIZE	DIM A	DIM B	PCS/UNITS PER BOX	WEIGHT PER C
CKR50	1/2"	1/2"	1-5/8"	1-1/8"	219	14.0
CKR75	3/4"	3/4"	1-3/4"	1-3/8"	168	21.3
CKR100	1"	1"	1-7/8"	1-11/16"	120	28.0
CKR125	1-1/4"	1-1/4"	2-1/4"	2-1/16"	66	48.5
CKR150	1-1/2"	1-1/2"	2-1/4"	2-1/4"	58	59.5
CKR200	2"	2"	2-3/8"	2-3/4"	33	78.9
CKR250	2-1/2"	2-1/2"	3-7/8"	3-5/8"	11	205.5
CKR300	3"	3"	4"	4-1/4"	8	263.0
CKR350	3-1/2"	3-1/2"	4-11/16"	4-11/16"	6	309.4
CKR400	4"	4"	4-15/16"	5-3/16"	4	393.4

PATENTED
U.S. Patent No.
8.129.633B1

